































Wipro Lighting brings to you highly energy efficient and high performance Cleanray range of LED luminaires for indoors and outdoors. This range not only creates stunning interiors but also vibrant outdoors. Now illuminate with more savings!







IrisLED Slim RO

LD80

recess mounted slim round LED panel

IrisLED Slim SQ

LD81

recess mounted slim square LED panel

APPLICATIONS

















ELECTRICAL DATA

CAT NO.	POWER (W)	CUTOUT DIMENSIONS (MM)	CASE LOT (IN NOS.)
LD80-200-XXX-60-XX / LD81	3	ø75 / 75 X 75	30
LD80-350-XXX-60-XX / LD81	6	ø108 / 108 X 108	18
LD80-530-XXX-60-XX / LD81	9	ø135 / 135 X 135	18
LD80-101-XXX-60-XX / LD81	12	ø157 / 157 X 157	12
LD80-131-XXX-60-XX / LD81	15	ø178 / 178 X 178	12
LD80-171-XXX-60-XX / LD81	18	ø178 / 178 X 178	06
LD81-281-XXX-60-XX	24	227 X 227	10

LED is an ever improving and evolving technology. Wipro is committed to bring you the best in LED technology. Data given is representative and can change.





IrisLED Slim RO SM

LD80

surface mounted slim round LED panel



IrisLED Slim SQ SM

LD81

surface mounted slim square LED panel

die-cast housing slim profile best-in-class system efficiency

ELECTRICAL DATA

CAT NO.	POWER (W)	CASE LOT (IN NOS.)
LD80-350-XXX-60-SM / LD81	6	18
LD80-101-XXX-60-SM / LD81	12	12
LD80-171-XXX-60-SM / LD81	18	6











SlimrisLED

CRDL14

recess mounted round slim LED downlighter

SquarisLED

CRDL15

recess mounted square slim LED downlighter

die-cast housing slim profile

long service life

APPLICATIONS





















ELECTRICAL DATA

CAT NO.	POWER (W)	CUTOUT DIMENSION (MM)	CASE LOT (IN NOS.)
CRDL14R005HP60 / CRDL15	6	ø90 / 90 x 90	12
CRDL14R010HP60 / CRDL15	11	ø115 / 115 x 115	12
CRDL14R015HP60 / CRDL15	17	ø140 / 140 x 140	12





CRCO₁₀

recess mounted LED luminaire with complete diffuser



ImmaculateLED Slim

CRCO23

recess mounted LED slim luminaire

APPLICATIONS















ELECTRICAL DATA

CAT NO.	POWER (W)	DIMENSIONS (MM)	CASE LOT (IN NOS.)
CRCO10R038HP57GL	36	565 x 565	02
CRCO23R036HP65G1	36	570 x 570	02

Suitable for Armstrong, Modular and POP/Gypsum ceiling. For POP/Gypsum ceiling please order frame separately. Order 9180P01025 for Aluminium and 9180P01089 for M.S. frame.

LED is an ever improving and evolving technology. Wipro is committed to bring you the best in LED technology. Data given is representative and can change.



seamless profile glare free uniform illumination



aesthetic design uniform light quality high energy efficiency



LED batten suitable for indoor applications
















ELECTRICAL DATA

IP20

CAT NO.	POWER (W)	CASE LOT (IN NOS.)
L20-111-XXX-65-NE - 2 feet	10	20
_L20-221-XXX-65-NE - 4 feet	18	20















ProLED Linear

LL13

high efficiency LED linear lamp

replacement of 36W T8 fluorescent lamp payback in 9 months

ProLED Compact

LL₁₈

high efficiency LED compact lamp

replacement of 36W CFL 2G11 4 pin payback in 13 months

easy to install instant start upto 55% energy savings 100 Lms per watt inbuilt electronic LED driver

WIOLED

channel suitable for ProLED lamp



APPLICATIONS













ELECTRICAL DATA

CAT NO.	POWER (W)	CASE LOT (IN NOS.)
LL13-181-650	18	12
LL13-181-65SE	20	12
WIO 921208	suitable for single 4ft lamp	20
WIO 922208	suitable for twin 4ft lamp	20
LL18-181-65PL	18	20

LED is an ever improving and evolving technology. Wipro is committed to bring you the best in LED technology. Data given is representative and can change.







compact design high energy efficiency excellent thermal management high performance driver with surge protection





SkylineLED

LR02

pressure die-cast LED streetlight

APPLICATIONS











ELECTRICAL DATA

IP66

POWER	CASE LOT
(W)	(IN NOS.)
20	08
	(W)



LED is an ever improving and evolving technology. Wipro is committed to bring you the best in LED technology. Data given is representative and can change.





AlphaLED

LF19

high performance LED floodlight

IP66 protection uniform light distribution virtually maintenance free service life

APPLICATIONS











CAT NO.	POWER (W)	CASE LOT (IN NOS.)	
LF19-471-060-57-XX	40	01	





IP65 high energy efficiency compact & aesthetic design





MoonLED RO

LW01

circular LED wall/ceiling light



MoonLED SQ

LW02

square LED wall/ceiling light

APPLICATIONS









ELECTRICAL DATA

CAT NO.	POWER (W)	CASE LOT (IN NOS.)
LW01-101-XXX-60-XX	9	10
LW02-101-XXX-60-XX	9	10



LED is an ever improving and evolving technology. Wipro is committed to bring you the best in LED technology. Data given is representative and can change.





FormzLED

LS06

flexible LED striplight

APPLICATIONS



OFFICES CONFERENCE ROOMS BANKS







ELECTRICAL DATA

IP20

CAT NO.	POWER (W)	LENGTH (M)
LS06-005-120-WH-50	5W per meter	5
LS06-005-120-WW-50	5W per meter	5
LS06-015-120-WH-50	15W per meter	5
LS06-015-120-WW-50	15W per meter	5

Order driver separately.

LG40-024 - 1 unit is suitable for 1 no (5m spool) of LS06-005. LG40-078 - 1 unit is suitable for 1 no (5m spool) of LS06-015.

LED is an ever improving and evolving technology. Wipro is committed to bring you the best in LED technology. Data given is representative and can change.



maintenance free

easy to install









WIPRO LIGHTING LEDEDGE

Get the Edge with LED Lighting Solutions for Indoors and Outdoors

- Eco-sustainability, Design & innovation, Green technology and Efficient lighting solutions
- Capability to service multi-locational accounts
- Service Commitment 35 branches and over 400 dedicated stockists
- Ease of contact through website
- Trustworthiness and Reliability of Wipro



Scan the QR code to download the app







Business Office:

Wipro Lighting, 5th floor, Godrej Eternia - C, old Pune-Mumbai road, Shivajinagar, Pune 411005. India. Tel.: 020-66098700, Fax: 020-66098777. E-mail: helpdesk.lighting@wipro.com

Registered Office:

Wipro Enterprises (P) Limited

'C' Block, CCLG Division, Doddakannelli, Sarjapur Road, Bangalore - 560035, India.

New Delhi: 011-41708121/29/9971117364/9899163896, Mumbai: 022-67213755/9739762999/9167992503, Bangalore: 080-41503260/41503268/9880100588 /8197730123/9632729977, Chennai: 044-32518016/24769653/9047297979/9791121986, Kolkata: 033-44045886/87/3420102239, Pune: 020-25510583/25535081/9819482448/9765410521, Hyderabad: 040-27176082/27178906/27178905/9819482448/9000102233, Chandigarh: 0172-50018734/2660714/9814350562/9216108102, Ludhiana: 9814350562, Karnal: 9814350562/9216108102, Dehradun: 9814350562/9216108102, Lucknow: 0522-2434352/09425072138/8874711820, Patna: 8420102239, Guwahati: 0361-2345927/9435010627, Jaipur: 0141-2280289/9928211211, Ahmedabad: 079-40073546/9898001521, Baroda: 9898001521/9099924867, Surat: 9898001521, Rajkot: 09998057866, Raipur: 0771 - 3265725/09425072138/9099812666, Indore: 0731-3299668/9425072138, Bhopal: 9425072138, Jabalpur: 9425072138, Jamshedpur: 8420102239, Bhubaneshwar: 8420102239, Vishakhapatnam: 9618456143, Nagpur: 0712-2569878/09425072138, Aurangabad: 9822192284/9765410521, Goa: 086260181133/9561706070, Hubli: 9765410521, Mangalore: 9961464188, Cochin: 9961464188, Combatore: 9789779179, Madurai: 9961464188

Innovation and Improvement are a way of life at Wipro. All rights reserved. Reproduction of this data in part or in whole without permission is prohibited. Care has been taken to ensure that the information content within is correct. We reserve the right to modify the product without prior intimation. Imitation of Registered Designs is a punishable offence.

Toll-free no: 1800-425-1969 www.wiprolighting.com

Follow us on Linked in