ELATELED CRCO10

Recess mounted LED luminaire with complete diffuser

SEAMLESS PROFILE WITH UNIFORM ILLUMINATION

55% ENERGY SAVINGS




WIPRO LED EDGE

_			
LIGHT SOURCE	DRIVER	OPTICS	THERMAL MANAGEMENT
Best-in-class LED technology High efficiency, LM 80 compliant LEDs Options in colour temperature	Specially designed for Indian power conditions Best-in-class design and manufacturing Complies to SELV design standards ensuring safety	Uniform and glare-free lighting Effective light distribution ensuring high performance	Special design for effective thermal management ensures long service life and consistent performance

ELATELFD

Recess mounted LED luminaire with complete diffuser













Clutter free ceiling

Luminaire blends unobtrusively with the ceiling and seamless profile gives a neat, clean and clutter free look to the ceiling enhancing the overall appearance of the space.

Enhanced Visual Harmony Performance

High efficiency LED A soft and soothing light with uniform grade diffuser ensures better light transmission illumination enriches the work environment and perfect diffusion of that helps in light. Thus enhances achieving the work the work environment. task productivity.

High Efficacy LEDs

High efficacy LEDs ensures optimum light output with less energy consumption and lesser Light Power Density(LPD).

SPECIFICATIONS

INSTALLATION

ACCESSORIES

10 pcs/box.


- White powder coated housing & frame in **CRCA** sheet
- High efficiency LED grade diffuser
- High efficacy LEDs for better light output
- Electronic driver pre-wired upto the terminal block

• Suitable for modular ceiling system

• For Gypsum/POP applications additional frame needs to be ordered separately. Order 9180P01025 for aluminium. Or order 9180P01089 for M.S. Case lot

• Designed and manufactured to comply with IS 10322 part 5/Sec 1 1987

DIMENSION DRAWING



All dimenions are in mm. Tolerance + 2 mm.

APPLICATIONS









Education



Hospital





ELECTRICAL DATA

IP 20

Product Code	System Wattage (W +/-5%)	Rated Voltage (V)	Mains Current (A)	Case Lot (in Nos)
CRCO10R038HP57GL	36	240	0.18	2
CRCO10R038HP57GL1	36	240	0.18	2

LED is an ever improving and evolving technology. Wipro is committed to bring you the best in LED technology. Data given is representative and can change.

Wipro Lighting, 5 floor, Godrej Eternia - C, Old Pune-Mumbai Road, Shivajinagar, Pune 411 005. Tel.: 020-66098700, Fax: 020-66098777. E-mail: helpdesk.lighting@wipro.com

Registered Office:

Wipro Enterprises (P) Limited, 'C' Block, CCLG Division, Doddakannelli, Sarjapur Road, Bangalore - 560035, India. Toll-free no: 1800-425-1969 www.wiprolighting.com Follow us on **Linked** in