

WhistlingLED Bollard | LB12, LB13

PREMIUM LED BOLLARD



Redefining outdoors
with enhanced quality
of light complimented
with delightful musical
and socialising
experiences



Wipro introduces an innovative socialising experience with Whistling Bollards - premium category functional lights for illuminating the pathways and enlightening the surroundings with musical notes. Designed for glare-free asymmetric distribution, the bollards focus the light on pathways and avoid scattering effect, giving the user an enigmatic experience.



- 1 ECO-FRIENDLY AND PLEASANT AESTHETICS**

Avoiding upward light pollution for the comfort of nocturnal creatures

Elegant body structure of the bollard adds to the beauty of the surroundings
- 2 SOCIALISING EXPERIENCE**

Light illuminates faces subtly along with the pathways with the usage of specialised lens made out of molded seamless premium diffuser for subtle and guided asymmetric distribution of light
- 3 MUSICAL SYMPHONY**


Add-on speaker module with wired connectivity to the amplifier
- 4 CORROSION PROOF BODY-MATERIAL**

Powder coated aluminum extrusion for superior aesthetics and rust proofing
- 5 INGRESS PROTECTION**

With IP65 construction, the bollard is protected from water, dust and insects




WHISTLING OYSTER LED BOLLARD LB12



Pole Ø 60-76mm
Pole to be ordered separately
All dimensions are in mm. Tolerance ± 2 mm

WHISTLING J LED BOLLARD LB13



Pole Ø 60-76mm
Pole to be ordered separately
All dimensions are in mm. Tolerance ± 2 mm

SPECIFICATIONS

Add-on Speaker module

Asymmetric dual optics with directional reflector

High efficiency transmission with specially designed, injection molded, seamless, asymmetric PC diffuser

Dark grey, pure polyester powder coated aluminum extruded housing

IP 65 potted driver and accessories pre-wired up to terminal block

High efficacy LEDs

IS 10322 part 5/Sec 1 1987 comply

APPLICATION



Campus
Lighting



Car
Parking



Resorts



Parks &
Gardens



Townships



Residential
Lighting

ELECTRICAL DATA

IP65

Product Code	System Wattage(w)	Rated Voltage (V)	Mains Current (A)	Case Lot (in nos.)	Approx Weight (kg)
LB12-880-XXX-30-05	7	240	0.03	01	3
LB12-131-XXX-30-05	11	240	0.04	01	3
LB13-880-XXX-30-05	7	240	0.03	01	3
LB13-131-XXX-30-05	11	240	0.04	01	3

*Available in 3000K & 6500K colour temperature options.
Also available in 5m & 8m length options.

WIPRO LIGHTING LEEDGE

Get the Edge with LED Lighting Solutions for outdoors through:

- Eco-sustainability, Design & innovation, Green technology and Efficient lighting solutions
- Capability to service multi-locational accounts
- Service Commitment - 19 branches and over 350 dedicated stockists
- Ease of contact through website
- Trustworthiness and reliability of Wipro



Scan the QR code
to download the app

New Delhi: 011-4170 8121/29, **Mumbai:** 022-6218 2000, **Chennai:** 95660 86333,
Bangalore: 080-4150 3260, **Kolkata:** 033-4404 5886/87, **Pune:** 020-2553 5081,
Hyderabad: 040-2717 6082, **Chandigarh:** 0172-5001 8734, **Jaipur:** 0141-2280 014/4910 879,
Lucknow: 0522-2434 352, **Baroda:** 0265-2395 830/35/36/41/45, **Ahmedabad:** 079-4007 3546,
Indore (MP): 98279 99668, **Raipur (CG):** 0771-3265 725, **Bhubaneswar:** 0674-6450 804,
Coimbatore: 98947 95836, **Nagpur:** 0712-2569 878, **Vishakhapatnam:** 96769 08080,
Cochin: 98957 08464.

Business Office

Wipro Lighting, 5th floor, Godrej Eternia - C,
old Pune-Mumbai highway, Shivajinagar, Pune 411 005. India.

(T) 020-66098700, (F) 020-66098777
helpdesk.lighting@wipro.com

Registered Office

Wipro Enterprises (P) Limited
'C' Block, CCLG Division, Doddakannelli, Sarjapur Road,
Bangalore - 560035, India.

Innovation and Improvement are a way of life at Wipro.
All rights reserved. Reproduction of this data in part or in whole without permission is
prohibited. Care has been taken to ensure that the information content within is correct.
We reserve the right to modify the product without prior intimation. Imitation of
Registered Designs is a punishable offence.

www.wiprolighting.com
Toll-free no: 1800-425-1969

Follow us on    

